

# Very suitable for skidloading!!

## Solomix2 VLS - L-VLS

**Trioliet mixer (trailer type) Solomix 2, models 1200 VLS, 1200-Low-VLS, 1600-Low-VLS, with two augers and adjustable chain conveyor at front**

### STANDARD FEATURES

- Two heavy-duty planetary drives • Hand jack • Open and low drawbar with clevis • Constant velocity PTO shaft • Large door opening • Four-five hardened knives per auger • Two manual restrictor blades • To be connected directly to tractor hydraulics • Left- or right-hand chain conveyor discharge • Two large wheels, tires 315/80 - 22.5 18 Ply (1200 VLS) • Two large wheels, tires 385/65 - 22.5 18 Ply (1200 L VLS and 1600 L VLS) • Hydraulic lift cylinder for chain extension (models R and L) • RL with mechanical operation left and hydraulic cylinder right

### Technical Data

Model	1200 VLS (R) (L)	1200-Low VLS (R) (L)	1600-Low-VLS (R) (L)
Capacity m <sup>3</sup> /Cu Ft.	<b>12/430</b>	<b>12/430</b>	<b>16/570</b>
Discharge	In height adjustable chain conveyor (at front)		
Overall length m./Inch	5.69/224"	6.01/240"	6.60/260"
Overall width m./Inch	2.15/85"	2.29/90"	2.44/96"
Overall height m./Inch	2.65/104"	2.45/98"	2.57/101"
Width outside wheels m./Inch	2.00/80"	2.25/90"	2.44/96"
Height of tub m./Inch	2.00/80"	1.88/74"	1.96/77"
Diameter of tub m./Inch	1.50/59"	1.70/67"	1.96/77"
Discharge height m./Inch**	0.72/29"	0.85-1.07/39"-78"	0.85-1.07/39"-78"
Length of chain conveyor (VLS) m./ft.	0.60/2	0.90/3	0.90/3
Number of knives per auger	4	4	5
Net weight kg./Lbs	4.200/9,260	4.700/10,360	6.000/13,225
Maximum load kg./Lbs	4.500/9,920	5.000/11,000	5.000/11,000
Power requirement PTO kW/HP	48/65	60/82	65/90
PTO Drive	540 RPM		
Scale system	3-point		
Width of chain conveyor m./Inch	0.75/30"		
Required hydraulic capacity	20 l/min., 170 bar/5,29 gallons/min 2465 psi		
Required tractor hydraulic	2 double acting valves		

\* Technical specifications regarding RL are different (on request) (R) = discharge at right hand side (RL) = discharge at both sides. (L) = discharge at left hand side \*\* Depending on length of chain extensions (variable from 2 ft - 6 ft)



Discharge by in height adjustable chain conveyor.

### ACCESSORIES

Electronic weighing system, Hydraulic restrictor blades, Reduction gearbox, Electric operation, Hay ring, Lighting set, Bowden cable control, Mineral chute, Magnets, Hydraulic jack, Rear pre-mix door.



Easy to load by Bobcat.



Trioliet reserves the right to make changes in design and specifications, or to add new features without obligation on implements before or after such changes are made.

