TRIOLIET
FEEDING TECHNOLOGY



TRIOTRAC L
FARMER EDITION

Self-propelled feed mixers

Trioliet. Invents for you..

The Triotrac L self-propelled feed mixer is known for its cutting and loading system. Over the years, this proven system has demonstrated its durability and outstanding energy efficiency, helping hundreds of farmers minimise feed losses at the silage clamp. With its robust construction and suspension, the machine is designed for several hours of comfortable daily operation on dairy and beef farms.

The Triotrac L Farmer Edition was developed with this principle in mind.
Many farmers do not need a particularly high-reaching loading arm or a six-cylinder engine, but still want a fast and efficient self-propelled feed mixer.

TWO TRIOTRAC L FARMER MODELS AVAILABLE

The Triotrac L Farmer Edition is available with capacities of 17 m^3 and 20 m^3 and includes the following standard features:

- Cutting system with cutting curve correction and a loading height of up to 4,5 m.
- Twin-auger mixing tub with the Dual Flow mixing principle for perfectly homogeneous rations.
- FPT four-cylinder engine delivering 147 kW / 200 hp.
- Front-wheel drive with a maximum speed of 25 km/h.
- Four-wheel steering.



TECHNICAL SPECIFICATIONS

Specifications	1700	2000
Capacity (m^3)	17	20
Length (m)	9,70	10,20
Width (m)	2,44	2,44
Height (m)	2,95	2,95
Maximum loading height (m)	4,50	4,50
Cutting width (m)	1,85	1,85
Cutting depth (m)	0,40	0,40
Maximum speed (km/h)	25	25
Tyre size	435/50R 22,5	435/50R 22,5

STANDARD FEATUYRES

U-shaped cutting system, Telescopic loading system with cutting curve correction, Two hydrostatically driven vertical Long-Life mixing augers with variable speed control, Loading conveyor with variable speed control, Hydrostatic drive with ECO-mode during road travel, Front and rear axle suspension, Front-wheel drive and four-wheel steering, FPT four-cylinder engine delivering 147 kW / 200 hp, All-round work lights, Comfortable, height-adjustable cab with an air-suspended seat, heating and air conditioning, Reversing camera, Cross conveyor with variable speed control.

TRIOLIET.COM

TRIOLIET
T: +31 541 57 21 21
E-mail: sales@trioliet.com